Applicant: Paul N. Stoving et al. Attorney's Docket No.: 08215-540001 / P03-026853

Serial No.: 10/802,409

Filed : March 16, 2004

Page : 2 of 5

# Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

## **Listing of Claims**:

1. (Previously presented) A vacuum switching device comprising:

a vacuum interrupter;

a current exchange housing adjacent to the vacuum interrupter;

a seal provided around the vacuum interrupter and the current exchange housing so as to define a cavity within the current exchange housing and adjacent to the vacuum interrupter; and

a capillary tube provided through the seal, the capillary tube disposed such that a first end of the capillary tube accesses the cavity and a second end of the capillary tube accesses an exterior of the seal.

- 2. (Previously presented) The vacuum switching device of claim 1 wherein the capillary tube comprises a syringe needle inserted through the seal.
- 3. (Previously presented) The vacuum switching device of claim 1 wherein the capillary tube is integrally formed into the seal during formation of the seal.
- 4. (Previously presented) The vacuum switching device of claim 1 wherein the second end of the capillary tube is open to an encapsulation material provided around the vacuum interrupter, the current exchange housing, and the seal.
- 5. (Original) The vacuum switching device of claim 4 wherein the encapsulation material includes a pre-filled, hot-curing, two-component epoxy resin.

#### 6-7. (Canceled)

Applicant: Paul N. Stoving et al. Attorney's Docket No.: 08215-540001 / P03-026853

Serial No.: 10/802,409 Filed: March 16, 2004

Page : 3 of 5

8. (Original) The vacuum switching device of claim 1 comprising an operating rod extending through the seal into the cavity, and operable to actuate the vacuum interrupter.

#### 9-17. (Canceled)

- 18. (Previously presented) A vacuum switching device comprising:
- a vacuum interrupter;
- a hollow housing adjacent to the vacuum interrupter;
- a seal provided around the vacuum interrupter and the hollow housing, the seal defining an air-filled cavity within the hollow housing; and
- a tube provided through the seal and including cured liquefied encapsulation material to block the passage of air between an exterior of the seal and the cavity.

## 19-21. (Canceled)

22. (Previously presented) The vacuum switching device of claim 18 wherein the tube comprises a syringe needle inserted through the seal.

### 23. (Canceled)

24. (Currently Amended) The vacuum switching device of claim 18 wherein:

the tube is disposed such that a first end of the tube accesses the cavity and a second end of the tube access an exterior of the seal, and

the second end of the tube is open to [[an]] a second encapsulation material provided around the vacuum interrupter, the hollow housing, and the seal.

25. (Currently Amended) The vacuum switching device of claim 24 wherein the second encapsulation material includes a pre-filled, hot-curing, two-component epoxy resin.

Applicant: Paul N. Stoving et al. Attorney's Docket No.: 08215-540001 / P03-026853

Serial No.: 10/802,409 Filed: March 16, 2004

Page : 4 of 5

26. (Previously presented) The vacuum switching device of claim 18 comprising an operating rod extending through the seal into the cavity, and operable to actuate the vacuum interrupter.

- 27. (Previously presented) The vacuum switching device of claim 1 wherein the capillary tube has an inner diameter of approximately 0.25 to 0.35 mm.
- 28. (Previously presented) The vacuum switching device of claim 1 wherein the capillary tube has a gauge from 23 to 26.